



ZEBRA

# 8000T Light-Weight 8 mil Tag

## FEATURES

- Thermal transfer, Tyvek® olefin 8.0 mil tag
- Some smear/scratch resistance
- Light weight film with high tear resistance
- Available in white (05066RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White spunbonded polyolefin	8.0 mil
TOTAL ± 10%		8.0 mil

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
N/A	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH

**Expected Exterior Life**  
1 year

## CHEMICAL RESISTANCE

Chemical		Suggested Ribbon		
		6000	5319	6100
Weak	Blood	●	●	●
	Body Fluid	●	●	●
	Salt Water	●	●	●
	Water	●	●	●
	Window Cleaner	●	●	●
Moderate	Alcohol	●	●	●
	Ammonia	●	●	●
	Bleach	●	●	●
	IPA	●	●	●
Harsh	Gasoline	NR	NR	NR
	Grease	NR	NR	NR
	Oil	NR	NR	NR
Extreme	Acetone	NR	NR	NR
	IR Reflow	NR	NR	NR
	MEK	NR	NR	NR
	TCE	NR	NR	NR
	Xylene	NR	NR	NR

## SUGGESTED APPLICATIONS

- Outdoor storage tags



- Water-immersed tags



● Recommended ● Test in Your Application NR Not Recommended

Tyvek is a registered trademark of E.I. du Pont de Nemours and Company.

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

