

# 8000T Tuff 7.0 mil Tag

# **FEATURES**

- · Thermal transfer, V-Max® polyolefin 7.0 mil tag
- Some smear/scratch resistance
- Good durability and chemical resistance
- Available in white (05025RM)

# **MATERIAL CONSTRUCTION**

Component	Description	Caliper
Facestock	Opaque white polyolefin	7.0 mil
	TOTAL ± 10%	7.0 mil

### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
N/A	-70° F to 200° F (-57° C to 93° C)	72° F (22° C) at 50% RH

# **Expected Exterior Life**

2 years

V-Max is a registered trademark of Van Leer Flexibles, Inc.

#### **CHEMICAL RESISTANCE**

		Suggested Ribbon	
	Chemical	6100	3200
Weak	Blood	•	•
	Body Fluid	•	•
	Salt Water	•	•
	Water	•	•
	Window Cleaner	•	•
Φ.	Alcohol	•	•
erat	Ammonia	•	•
Moderate	Bleach	•	•
	IPA	•	•
Harsh	Gasoline	NR	NR
	Grease	NR	NR
	Oil	NR	NR
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

■ Recommended • Test in Your Application NR Not Recommended

#### **SUGGESTED APPLICATIONS**

Outdoor storage tags



· Water-immersed tags



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies









