

## **8000D Linerless**



Media Type	Label	✓
	Receipt	
	Tag	
	Wristband	
Material Type	Paper	✓
	Synthetic	
Printing Technology	Direct Thermal (no Ribbon Required)	✓
	Thermal Transfer (Ribbon Required)	
Finish	Matte	
	Gloss	✓

	Permanent	✓
Adhesive Type	Removable	
	No Adhesive	
Environment	Indoor	✓
	Outdoor	
Properties	Cold Temperature	✓
	Deep Freeze	✓
	High Temperature	
	Ultra High Temperature	
	High Tack	
	Chemical Resistance	•

Note: 8000D Linerless will require a linerless roller for the printer and is not recommended for applications involving chemicals.

#### **Additional Features**

- No ribbon required for direct thermal printing, therefore only one stock item needed
- Absence of a liner allows for more labels per roll and no waste having both environmental and safety implications in some applications
- Good scratch and smear resistance
- Excellent print quality when used in a Zebra linerless printer
- BPA free, BPS free
- Latex free adhesive

#### **Suggested Applications**

- Product and price labelling in retail applications
- Mobile point of sale labelling
- Work in progress labelling
- Applications that do not allow the use of a liner

# **Technical Specifications**

	Description		Caliper
Facestock	Smooth white silicone topcoated paper	r	76 microns
Adhesive	Permanent rubber adhesive		30 microns
		Total	106 microns ±10%







Recommended Zebra Printers: QL and QLn Series mobile printers

4°C

**Minimum Application Temperature:** 

When the label is applied, the environment and surface should be above this temperature

> **Service Temperature Range:** -40°C to 60°C

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 6 months duration when stored at 22°C at

Storage of product before use 50% RH

**Expected Life Span in Application:** Indoor use, up to 1 year

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

### **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order LD-R2LS5W and LD-R4LF5P from the ZipShip price list.



