



**ZEBRA**

# 8000T Checkerboard Gloss

## FEATURES

- Thermal transfer, silver, gloss polyester label with a tamper-proof adhesive that leaves a checkerboard pattern when label is removed
- Excellent smear/scratch resistance
- Excellent durability and chemical resistance
- Retains void characteristic at temperatures up to 80° C
- Available in silver (05662RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	Silver gloss polyester	2.0 mil
Adhesive	Permanent, tamper-evident acrylic-based	0.8 mil
Liner	50 lb. semi-bleached, kraft stock	3.2 mil
<b>TOTAL ± 10%</b>		<b>7.0 mil</b>

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
50° F (10° C)	-40° F to 176° F (-40° C to 80° C)	72° F (22° C) at 50% RH

### Expected Exterior Life

Not recommended for outdoor use

## CHEMICAL RESISTANCE

		Suggested Ribbon	
Chemical		5095	5100
Weak	Blood	●	●
	Body Fluid	●	●
	Salt Water	●	●
	Water	●	●
	Window Cleaner	●	●
Moderate	Alcohol	●	●
	Ammonia	●	●
	Bleach	●	●
	IPA	●	●
Harsh	Gasoline	●	●
	Grease	●	●
	Oil	●	●
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

### 80°C Void Performance on Stainless Steel

Dwell Time	% Voiding	% Adhesive Transfer
24 hours at RT	100%	95%

## SUGGESTED APPLICATIONS

- Product Identification



- Tamper evident security labels



- Capital asset labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application

