



**ZEBRA**

# 8000T Multi-Removable

## FEATURES

- Thermal transfer, paper label with a multi-removable adhesive that offers dual functionality; provides permanent adhesion to corrugate surfaces but also allows clean removal from glass surfaces
- Excellent print quality
- Topcoating is suitable for fanfolding
- Available in white (65171RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth topcoated paper	3.2 mil
Adhesive	Multi-removable, acrylic-based	0.9 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
<b>TOTAL ± 10%</b>		<b>6.6 mil</b>

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
25° F (-4° C)	-20° F to 200° F (-29° C to 93° C)	72° F (22° C) at 50% RH

### Expected Exterior Life

Not recommended for outdoor use

## CHEMICAL RESISTANCE

	Chemical	Suggested Ribbon	
		6000	2000
Weak	Blood	●	●
	Body Fluid	●	●
	Salt Water	●	●
	Water	●	●
	Window Cleaner	●	●
Moderate	Alcohol	NR	NR
	Ammonia	NR	NR
	Bleach	NR	NR
	IPA	NR	NR
Harsh	Gasoline	NR	NR
	Grease	NR	NR
	Oil	NR	NR
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Shelf labeling 
- Work in process labeling 
- Product identification 

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

