



ZEBRA

# 8000T Piggyback

## FEATURES

- Thermal transfer, piggyback, paper label with a permanent acrylic adhesive
- Excellent high speed print quality
- Special constructions allows for removing the label, leaving the liner, and re-applying the second liner to a final application
- Available in white (05286RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White coated paper	3.1 mil
Adhesive	Permanent, acrylic-based	0.7 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
Adhesive	Permanent, acrylic-based	0.7 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
<b>TOTAL ± 10%</b>		<b>9.5 mil</b>

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
25° F (-4° C)	-65° F to 200° F (-54° C to 93° C)	72° F (22° C) at 50% RH

### Expected Exterior Life

Not recommended for outdoor use

## CHEMICAL RESISTANCE

Chemical		Suggested Ribbon		
		6000	2000	6100
Weak	Blood	●	●	●
	Body Fluid	●	●	●
	Salt Water	●	●	●
	Water	●	●	●
	Window Cleaner	●	●	●
Moderate	Alcohol	NR	NR	NR
	Ammonia	NR	NR	NR
	Bleach	NR	NR	NR
	IPA	NR	NR	NR
Harsh	Gasoline	NR	NR	NR
	Grease	NR	NR	NR
	Oil	NR	NR	NR
Extreme	Acetone	NR	NR	NR
	IR Reflow	NR	NR	NR
	MEK	NR	NR	NR
	TCE	NR	NR	NR
	Xylene	NR	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Labeling of packaging material including corrugate, plastic, and metal



- Product identification



- Work in process labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

