



PRESSIZA 25

PERFORMANCE GUIDE

Features

- Matte finished metallic film featuring excellent tear strength, heat resistance, dimensional stability, opacity and chemical resistance
- Designed for printing with most solvent and some water-based flexographic inks
- Suitable for thermal transfer printing applications with select thermal transfer ribbons
- Bleached, supercalendered paper stock with very good diecutting and matrix stripping properties.
- Suitable for backprinting with standard inks

Suggested applications

Product identification labels
Barcodes and rating plates
Work in progress labels (WIP)
Property identification and asset tags
Durable goods labeling UL and ULc recognized for indoor and outdoor use

Face

Caliper 0.0020 +/- 10% inches

Adhesive

Thickness 0.0009 +/- 10% inches
Peel Adhesion Stainless Steel: 50.6 oz/in

Temperature Ranges

Minimum Application +50°F (10°C)
Service Ranges -40°F to 302°F (-40°C to 150°C)

Liner

Caliper 0.0032 +/- 10% inches
Basis Weight 53.9 lbs.
(24" x 36" 500 sheets)

Important:

The substances listed in article 4 lid 1 of 2002/95/EU (RoHS) are not intentionally used in this product. The concentration limits of these substances will not exceed the set maximum concentration limits as provided in the proposed amendment for 2002/95/EU.

Shelf Life

Unless otherwise specified in this document, ideally store at 72°F and 50% RH



rsimexico.com



Contacto

contacto@rsimexico.com
Teléfono Tijuana: 664-215-0679
Teléfono Puebla: 222-225-6594

