



PRESSIZA I05

PERFORMANCE GUIDE

Features

- Facestock contact with noxious fumes from chemicals, lift trucks, etc. should be avoided. After ink-jet printing, the ink-jet receptive coating remains absorptive to many liquids that can stain the facestock.
- Care should be taken to avoid facestock contact with such liquids, or the printed facestock can be covered with a protective overlamine or clear coat.
- The above are typical technical values and are given in good faith based upon our most up to date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused using the product.

Adhesive: RP37

Type: Clear permanent adhesive.

Composition: Emulsion acrylic.

Use: Designed specifically for applications requiring good initial tack and ultimate adhesion as well as good heat resistance.

Approvals and Certifications

BS5609 compliance with Epson inks for drum label sections 2 and 3.

Product	Polyjet matte white pp rp37 3.2 mil white kraft
Sales Code	SY848A
Description	Polyjetmatte white pp rp37 3.2 mil white kraft

Substance weight	132 lbs./ream (25" x 38")
Caliper	7.7 mil



Shelf life

From the date of manufacture: 2 years at 68°F and RH 50%.

Limitations

Limited adhesion at low temperatures. The highest end-use temperature must be separately checked together with the face material.



rsimexico.com



Contacto

contacto@rsimexico.com
Teléfono Tijuana: 664-215-0679
Teléfono Puebla: 222-225-6594

