



PRESSIZA 40

PERFORMANCE GUIDE

Features

- Clear top coated polypropylene film with a quick tack permanent adhesive and a 2.45 semi-bleached calendared kraft liner
- 2 mil clear polypropylene film top coated film for superior graphics
- Permanent acrylic emulsion with aggressive initial tack, excellent ultimate adhesion and mandrel hold
- A semi-bleached calendared kraft liner excellent for die cutting, stripping and label dispensing. Primarily for roll-to-roll applications

Suggested applications

Label applications requiring a semiconformable clear film in market segments: food, cosmetic, beverage, household cleaner and more.

Face

Caliper 0.002 +/- 10% inches

Adhesive

Thickness 0.0007 +/- 10% inches

Peel Adhesion 2.6

Temperature Ranges

Minimum Application +25°F (-4°C)

Service Ranges -75°F to +200°F (-59°C to +93°C)

Liner

Caliper 0.00245 +/- 10% inches

Basis Weight 40 +/- 10% lbs.
(24" x 36" 500 sheets)

Shelf Life

One year when stored at 72°F and 50% R.H.



rsimexico.com



Contacto

contacto@rsimexico.com
Teléfono Tijuana: 664-215-0679
Teléfono Puebla: 222-225-6594

