



PRESSIZA 51

PERFORMANCE GUIDE

Features

- Homogeneously pigmented white facestock featuring excellent tear strength, heat resistance, dimensional stability, opacity, and chemical resistance
- High performance, clear permanent emulsion acrylic pressure sensitive adhesive with balanced adhesion to a wide variety of substrates
- Medium tack and excellent chemical and UV resistance for outdoor industrial applications
- Bleached, super calendered paper stock with very good diecutting and matrix stripping properties
- Used for standard roll-to-roll applications

Face

Caliper 0.0020 +/- 10% inches

Adhesive

Thickness 0.0010 +/- 10% inches

Peel Adhesion Stainless Steel: 32.0 oz/in

Temperature Ranges

Minimum Application +50°F (10°C)

Service Ranges -40°F to 302°F (-40°C to 150°C)

Liner

Caliper 0.0032 +/- 10% inches

Basis Weight 54.5 lbs.
(24" x 36" 500 sheets)

Shelf Life

Unless otherwise specified in this document, ideally store at 72°F and 50% RH

Suggested applications

- Product identification
- Barcodes
- WIP (Workinprocess) tracking labels
- Asset tags

Important:

The substances listed in article 4 lid 1 of 2002/95/EU (RoHS) are not intentionally used in this product. The concentration limits of these substances will not exceed the set maximum concentration limits as provided in the proposed amendment for 2002/95/EU.



rsimexico.com



Contacto

contacto@rsimexico.com
Teléfono Tijuana: 664-215-0679
Teléfono Puebla: 222-225-6594

