



PRESSIZA A03

PERFORMANCE GUIDE

Features

- 3 Mil Matte White Synthetic Paper is a matte finished opaque white polypropylene synthetic material with the look and feel of paper and the moisture resistance of a film
- Clear general purpose emulsion acrylic permanent adhesive featuring good initial tack and ultimate adhesion to a wide variety of substrates
- Bleached, super calendered paper stock with very good diecutting and matrix stripping properties
- Used for standard roll-to-roll applications
- Not recommended for sheeting

Face

Caliper 0.0030 +/- 10% inches

Adhesive

Thickness 0.0008 +/- 10% inches

Peel Adhesion Stainless Steel: 44 oz/inch

Temperature Ranges

Minimum Application +10° F (-12°C)

Service Ranges -40° F to +300° F (-40°C to +149°C)

Liner

Caliper 0.0032 +/- 10% inches

Basis Weight 54.5 lbs per ream
(24" x 36" 500 sheets)

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Suggested applications

- Decals and product labels
- Nameplates
- WIP labels
- Shelf, bin, and other warehouse labels

Important:

The substances listed in article 4 lid 1 of 2002/95/EU (RoHS) are not intentionally used in this product. The concentration limits of these substances will not exceed the set maximum concentration limits as provided in the proposed amendment for 2002/95/EU.



rsimexico.com



Contacto

contacto@rsimexico.com
Teléfono Tijuana: 664-215-0679
Teléfono Puebla: 222-225-6594

