



# PRESSIZA A07

## PERFORMANCE GUIDE

### Features

- Ultra smooth thermal transfer coated facestock which provides premium barcode printing for high and medium speed printers
- Smudge resistance has been optimized for a coated paper, but caution is recommended with contact scanners
- Features excellent high speed/wide web converting characteristics
- Suitable for applications where compliance with FDA 175.105 is required
- Bleached, calendered kraft stock featuring high internal strength, toughness, and tear resistance
- Used primarily for roll-to-roll label applications

### Suggested applications

Rubber-based adhesive featuring high initial tack and ultimate bond strength to a wide variety of substrates, including low surface energy plastics, treated glass, and corrugated cardboard

### Face

Caliper 0.0030 +/- 10% inches

### Adhesive

Thickness 1.0 mil

Peel Adhesion HDPE: 3.72 lbs

### Temperature Ranges

Minimum Application +25° F (-4°C)

Service Ranges -65° F to +160° F (-54°C to +71°C)

### Liner

Caliper 0.0024 +/- 10% targe

Basis Weight 39.1# per ream +/- 10%  
(24" x 36" 500 sheets)

### Important:

The FSC® certification ensures that products come from well managed forests that provide environmental, social, and economic benefits. The FSC® chain of custody certification verifies that FSC® certified material is identified or kept segregated from non-certified or non-controlled material through this chain.

### Shelf Life

Unless specified otherwise in this document, ideally stored at 72°F at 50% RH



[rsimexico.com](http://rsimexico.com)



### Contacto

contacto@rsimexico.com  
Teléfono Tijuana: 664-215-0679  
Teléfono Puebla: 222-225-6594

