



PRESSIZA A25

PERFORMANCE GUIDE

Features

- 2 Mil Matte Chrome Polyester TC is a matte finished metallic film featuring excellent tear strength, heat resistance, dimensional stability, opacity and chemical resistance
- Designed for printing with most solvent and some waterbased flexographic inks
- Suitable for thermal transfer printing applications with select thermal transfer ribbons
- An excellent general purpose industrial grade clear permanent acrylic adhesive
- Features high initial tack to most high and medium surface energy substrates
- Bleached, supercalendered paper stock with very good diecutting and matrix stripping properties
- This liner should not be used in fanfolded label applications and is not recommended for back printability

Face

Caliper 0.0020 +/- 10% inches

Adhesive

Thickness 0.0008 +/- 10% inches

Peel Adhesion Stainless Steel: 35.8 oz/inch

Temperature Ranges

Minimum Application +25° F (-4°C)

Service Ranges -40° F to +300° F (-40°C to +149°C)

Suggested applications

- Product identification labels
- Barcode labels
- Rating plates
- Work in process (WIP) labels
- Property identification or asset tags
- Durable goods labeling
- Recognized for UL 969 component labels.

This product is UL Recognized and CSA Accepted for indoor and outdoor applications. For specific recognition or acceptance details, consult UL file MH17205 and CSA file 97198

Important:

The substances listed in article 4 lid 1 of 2002/95/EU (RoHS) are not intentionally used in this product. The concentration limits of these substances will not exceed the set maximum concentration limits as provided in the proposed amendment for 2002/95/EU.

Liner

| | |
|--|-----------------------|
| Caliper | 0.0032 +/- 10% inches |
| Basis Weight (24" x 36" 500 sheets) | 54.5 lbs per ream |

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH



Contacto