



PRESSIZA R01

PERFORMANCE GUIDE

Features

- Direct thermal smooth, bright white paper with a high sensitivity thermal layer
- Rubber based adhesive featuring high initial tack and ultimate bond strength to a wide variety of substrates, including low surface energy plastics, glass, and corrugated cardboard (engineered specifically for cold, damp environments typical of dairy environments)
- Bleached calendered kraft stock featuring high internal strength, toughness and tear resistance
- Used primarily for roll-to-roll label applications

Face

Caliper 0.0032 +/- 10% inches

Adhesive

Thickness 1.0 mil
Peel Adhesion HDPE: 1.8 lbs

Temperature Ranges

Minimum Application +25° F (-4°C)
Service Ranges -65° F to +160° F (-54°C to +71°C)

Liner

Caliper 0.0024 +/- 10% targe
Basis Weight 39.1# per ream +/- 10%
(24" x 36" 500 sheets)

Shelf Life

Unless specified otherwise in this document, ideally stored at 72°F at 50% RH

Suggested applications

Specifically designed to perform well in service counter and caseready deli applications, with resistance to moisture, heat, PVC, and other common contaminates.

This product is also well suited for parcel delivery and industrial case distribution where moderate resistance to moisture, stretch wrap, and abrasion is required.

Important:

This adhesive is suitable for applications which require compliance with FDA 175.105. This section covers applications where incidental contact between food and the adhesive could occur.



rsimexico.com



Contacto

contacto@rsimexico.com
Teléfono Tijuana: 664-215-0679
Teléfono Puebla: 222-225-6594

