



ZEBRA

PolyPro 4000T 8.5mil Tag

FEATURES

- Thermal transfer, smudgeproof Kimdura® topcoated 8.5 mil polypropylene tag
- Good smear/scratch resistance
- Excellent chemical resistance
- Available in white (05127RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White matte topcoated polypropylene	8.5 mil
TOTAL ± 10%		8.5 mil

FACESTOCK TENSILE STRENGTH

- Machine direction: 54 psi
- Transverse direction: 160 psi

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
NA	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH

EXPECTED EXTERIOR LIFE

2 year

CHEMICAL RESISTANCE

		Suggested Ribbon		
Chemical		6100	3200	6200
Weak	Blood	●	●	●
	Body Fluid	●	●	●
	Salt Water	●	●	●
	Water	●	●	●
	Window Cleaner	●	●	●
Moderate	Alcohol	●	●	●
	Ammonia	●	●	●
	Bleach	●	●	●
	IPA	●	●	●
Harsh	Gasoline	●	●	●
	Grease	●	●	●
	Oil	●	●	●
Extreme	Acetone	●	●	●
	IR Reflow	●	●	●
	MEK	●	●	●
	TCE	●	●	●
	Xylene	●	●	●

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Self-locking tags for greenhouse and nursery use



- Outdoor storage tags for wire, cable and fabricated parts



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

