

# PRESSIZA 04

## PERFORMANCE GUIDE



### Features

- Ultra smooth coated facestock which provides premium barcode printing for high and medium speed printers
- It offers excellent initial tack and ultimate adhesion, especially at lower temperatures, without sacrificing highspeed converting
- Bleached, calendered kraft stock featuring high internal strength, toughness, and tear resistance
- Used primarily for roll-to-roll label applications

### Suggested applications

Designed for excellent adhesion to corrugated cardboard and superior adhesion to plastics

### Face

Caliper 0.0030 +/- 10% inches

### Adhesive

Thickness 0.0007 +/- 10% inches

Peel Adhesion Stainless Steel: 2.6

#### Temperature Ranges

Minimum Application +30° F (-1° C)

Service Ranges 65° F to +200° F (18° C to 93° C)

### Important:

Meets the requirements of FDA CFR 175.105 for indirect food contact. Compliance to this regulation permits the use of this adhesive in applications for which the adhesive either (1) is separated from the food by a functional barrier, which will prevent the migration of any of the adhesive components to the food, or (2) has incidental contact with food limited to the trace amount at the seams or the edges of the label.

### Liner

Caliper 0.00247 +/- 10% inches

Basis Weight 40.6# per ream +/- 10%  
(24" x 36"/500 sheets)

### Shelf Life

One year when stored at 72° F and 50% R.H.

**TIJUANA:** (664) 215.0679

**PUEBLA:** (222) 225.6594

**HERMOSILLO:** (662) 369.7306

[comunicacion@rsimexico.com](mailto:comunicacion@rsimexico.com)

