

PRESSIZA 05

PERFORMANCE GUIDE

pressiza®

Features

- Premium thermal transfer paper construction with a removable adhesive
- Bright white, coated facestock designed for high-speed thermal transfer printing
- General-purpose acrylic based removable adhesive with excellent long-term removability from a wide variety of surfaces
- Semi-bleached calendared kraft liner excellent for die cutting, stripping and label dispensing. Primarily for roll-to-roll applications

Suggested applications

Intended for thermal transfer label applications requiring a removable adhesive. *Compatible with most thermal transfer ribbons designed for coated papers.

NOT RECOMMENDED FOR MANDREL APPLICATIONS

Face

Caliper 0.0029 +/- 10% inches

Adhesive

Thickness 0.0007 +/- 10% inches

Peel Adhesion Stainless Steel: 0.7

Temperature Ranges

Minimum Application 25°F (-4°C) *on most surfaces

Service Ranges -40 to 200°F (-40°C to 93°C)

Important:

Always pretest removable adhesives for suitability in each particular end use application

Liner

Caliper 0.00245 +/- 10% inches

Basis Weight 40 +/- 10%
(24" x 36" 500 sheets)

Shelf Life

One year when stored at 72° F and 50% R.H.

This information is confidential, and restricted for the internal use of RSI México customers for informative purposes, and can not be reproduced or communicated to third parties without our written authorization.

TIJUANA: (664) 215.0679

PUEBLA: (222) 225.6594

HERMOSILLO: (662) 369.7306

comunicacion@rsimexico.com

