

PRESSIZA R03

PERFORMANCE GUIDE



Features

- Heat set, biaxially oriented, coextruded polypropylene film, with good opacity and a bright white high gloss background
- The surface has been topcoated to provide superior printability by UV and waterbased flexographic, gravure, silkscreen and letterpress processes, using a wide variety of different inks
- Specially formulated acrylic adhesive designed for ease of removability from plastic packaging while maintaining good peel performance
- Bleached supercalendered kraft stock featuring high internal strength, toughness and tear resistance
- Used primarily for roll-to-roll label applications

Face

Caliper 0.0023 +/- 10% inches

Adhesive

Thickness 2.0 mil

Peel Adhesion Stainless Steel: 0.87 lbs

Temperature Ranges

Minimum Application +40° F (+4°C)

Service Ranges 0° F to +200° F (-18°C to +93°C)

Liner

Caliper 0.0025 +/- 10% target

Basis Weight 42# per ream +/- 10%
(24" x 36" 500 sheets)

Shelf Life

Unless specified otherwise in this document, ideally stored at 72°F at 50% RH

Suggested applications

This facestock has excellent moisture resistance, and good diecutting and dispensing characteristics

Important:

This adhesive is suitable for applications which require compliance with FDA 175.105. This section covers applications where incidental contact between food and the adhesive could occur. Title 21, Section 175.105 of the Code of Federal Regulations (21 CFR 175.105). Compliance to this regulation permits the use of this adhesive in applications for which the adhesive either (1) is separated from the food by a functional barrier, which will prevent the migration of any of the adhesive components to the food, or (2) has incidental contact with food limited to the trace amount at the seams or the edges of the label.

This information is confidential, and restricted for the internal use of RSI México customers for informative purposes, and can not be reproduced or communicated to third parties without our written authorization.

TIJUANA: (664) 215.0679

PUEBLA: (222) 225.6594

HERMOSILLO: (662) 369.7306

comunicacion@rsimexico.com

