



ZEBRA

6200 Standard Resin Ribbon

A standard resin ribbon formulation that produces images resistant to most harsh environments: smearing, moisture, abrasion, extreme temperature and chemicals when printed on Zebra’s gloss paper and gloss synthetic label and tag materials.

UL/ cUL / CSA Certifications with the following materials:

- Z-Supreme 2000T (UL, cUL)
- Z-Supreme 4000T (UL, cUL)
- Z-Ultimate® 4000T White & Silver (UL, cUL, CSA)
- Z-Ultimate® 2000T White (UL, cUL)
- Z-Xtreme 4000T White & Silver (UL, cUL, CSA)
- Z-Xtreme 4000T High-Tack White & Silver (UL, cUL, CSA)
- Z-Xtreme 2000T White, Silver & Clear (UL, cUL)



SUGGESTED APPLICATIONS

- Labels which are repeatedly wand-scanned



- Shelf and scan-pallet labels



- Labels subject to abrasion or friction



- Outdoor labeling applications in extreme environments



- Chemical drum labeling applications



- Labels exposed to water, steam, alkali or acid solutions



TECHNICAL SPECIFICATIONS

Attribute	Specification
Color	Black
Ink Formulation	Resin
Base Film	Polyester
Base Film Caliper	4.5 microns
Total Caliper	6.9 microns +/- 10%
Scanning Capabilities	IR and Visible Light

Recommended Storage Conditions: 72° F (22° C) at 50% RH

Shelf Life 1 year

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in

