



ZEBRA

Z-Perform 1000T Tag

FEATURES

- Thermal transfer, smooth, uncoated paper tag
- Recommended for printing applications up to 4 inches per second
- Available in 7.5mil (05168RM) and 9.5mil thickness (05242RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth uncoated thermal transfer paper	7.5 / 9.5 mil
TOTAL ± 10%		7.5 / 9.5 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
NA	-50°F to 200°F (-46°C to 93°C)	72° F (22° C) at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

Chemical	Suggested Ribbon			
	6000	2000	6100	
Weak	Blood	●	●	●
	Body Fluid	●	●	●
	Salt Water	●	●	●
	Water	●	●	●
	Window Cleaner	●	●	●
Moderate	Alcohol	NR	NR	NR
	Ammonia	NR	NR	NR
	Bleach	NR	NR	NR
	IPA	NR	NR	NR
Harsh	Gasoline	NR	NR	NR
	Grease	NR	NR	NR
	Oil	NR	NR	NR
Extreme	Acetone	NR	NR	NR
	IR Reflow	NR	NR	NR
	MEK	NR	NR	NR
	TCE	NR	NR	NR
	Xylene	NR	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Retail hang tags



- General purpose ticketing



- Work in process tagging



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

