



**ZEBRA**

# Z-Select 4000T Tag

## FEATURES

- Thermal transfer, premium, topcoated, ultra smooth paper tag
- Excellent high speed print quality
- Topcoating is suitable for fanfolding
- Available in 5mil (05396RM), 7mil (05209RM), 9mil (05274RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth topcoated direct thermal paper	5.0 mil 7.0 mil 9.0 mil
<b>TOTAL ± 10%</b>		<b>5.0 mil 7.0 mil 9.0 mil</b>

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
NA	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH

### Expected Exterior Life

Not recommended for outdoor use

## CHEMICAL RESISTANCE

	Chemical	Suggested Ribbon		
		6000	2000	6100
Weak	Blood	●	●	●
	Body Fluid	●	●	●
	Salt Water	●	●	●
	Water	●	●	●
	Window Cleaner	●	●	●
Moderate	Alcohol	NR	NR	NR
	Ammonia	NR	NR	NR
	Bleach	NR	NR	NR
	IPA	NR	NR	NR
Harsh	Gasoline	NR	NR	NR
	Grease	NR	NR	NR
	Oil	NR	NR	NR
Extreme	Acetone	NR	NR	NR
	IR Reflow	NR	NR	NR
	MEK	NR	NR	NR
	TCE	NR	NR	NR
	Xylene	NR	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Packing lists
- Retail hang tags
- General purpose ticketing
- Work in process tagging

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

